



Conforms to Regulation (EC) No. 1907/2006 - United Kingdom (UK)

SAFETY DATA SHEET

JET-LUBE EXTREME

Product classified as hazardous according to NOHSC classification

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Product Name: JET-LUBE EXTREME
Use of the substance/preparation: Tool Joint, Drill Rod & Anti-Seize Thread Compound (petroleum based), lubricant
Company/undertaking identification
Manufacturer: Jet-Lube, Inc.
 4849 Homestead Rd., Suite 232
 Houston, TX 77028
 Email: doldiges@jetlube.com USA Corporate phone: (713) 670-5700
Australian Contact: Xtex Pty. Ltd
 ABN 40 121 722 236
 80 Daly Street
 Ascot, WA 6104 1300-00-9839 phone 0437-272-490 mobile
Emergency telephone numbers: NHS DIRECT in the UK USA: CHEMTREC: (800) 424-9300
 Emergency number: 08454647 Outside US (Chemtrec): (703) 527-3887
 Xtex Pty. Ltd 1300-00-XTEX

2. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification: Not classified
Physical/chemical hazards: Not applicable
Human health hazards: Not applicable
Environmental hazards: Not applicable

See section 11 for more detailed information on health effects and symptoms.

3. Composition /information on ingredients

<u>Substance/preparation:</u> Preparation				
Ingredient name	CAS Number	%	EC Number	Classification
Lubricating grease (petroleum base)	74869-21-9	50 - 70	278-011-7	Not classified
graphite, natural	7782-42-5	10 - 15	231-95-3	Not classified
limestone	1317-65-3	5 - 10	215-279-6	Not classified
copper	7440-50-8	5 - 10	231-159-6	N; R50
talco, not containing asbestiform fibers	14807-96-6	1 - 5	238-877-9	Not classified
potassium aluminum silicates	12001-26-2	1 - 5		Not classified
molybdenum disulfide	1317-33-5	1 - 5	215-263-9	Not classified

3a. Lubricating Grease Composition /information on ingredients

<u>Substance/preparation:</u> Preparation				
Ingredient name	CAS Number	%	EC Number	Classification
Naphthenic Distillates	64742-52-5	54-76	255-155-0	Not classified
Hydrotreated residual Oils	64742-57-0	5 - 10	265-101-6	Not classified
Calcium (C12-C22) sulfonates	26264-06-2	5-10	247-557-8	Not classified
Calcium Carbonate	471-34-1	10-15	207-439-9	Not classified
Calcium Borate	13701-64-9	2-5	237-224-5	Not classified
Calcium 12-hydroxystearate	3159-62-4	2-5	221-605-8	Not classified
Calcium Phosphates	10103-46-5	0-1	233-283-6	Not classified
polyisobutylene	9003-29-6	0-1	Polymer	Not classified

The Petroleum Oils and additives do not require carcinogenic listing.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Obtain medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

See section 11 for more detailed information on health effects and symptoms.

5. Fire-fighting measures

Extinguishing media: Use an extinguishing agent suitable for the surrounding fire.
Special exposures hazards: No specific hazard.
Hazardous thermal decomposition products: These products are carbon oxides (CO, CO₂), sulphur oxides (SO₂, SO₃, etc.). Some metallic oxides.

JET-LUBE EXTREME

Special protective equipment for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions:

Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.

Environmental precautions:

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up:

If emergency personnel are unavailable, contain spilt material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain material to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

7. Handling and storage

Handling:

Wash thoroughly after handling.

Storage:

Keep container tightly closed. Keep container in a cool, well-ventilated area.

Packaging materials

Recommended:

Use original container.

Specific uses:

Not available.

8. Exposure controls/personal protection

Ingredient Name:

graphite, natural

Occupational exposure limits

EH40-WEL (United Kingdom (UK), 1/2005)

TWA: 10 mg/m³ 8 hour/hours. Form: Inhalable fraction

STEL: 4 mg/m³ 15 minute/minutes. Form: Respirable fraction

limestone

EH40-WEL (United Kingdom (UK), 9/2006)

TWA: 10 mg/m³ 65534 times per shift, 8 hour/hours. Form: Inhalable fraction

STEL: 4 mg/m³ 65534 times per shift, 15 minute/minutes. Form: Respirable fraction

copper

EH40-WEL (United Kingdom (UK), 9/2006). Notes: As Cu

TWA: 1 mg/m³ 65534 times per shift, 8 hour/hours.

STEL: 2 mg/m³ 65534 times per shift, 15 minute/minutes

talc, not containing asbestiform fibers

EH40-WEL (United Kingdom (UK), 9/2006)

TWA: 1 mg/m³ 65534 times per shift, 8 hour/hours. Form: Respirable fraction

potassium aluminum silicates

EH40-WEL (United Kingdom (UK), 9/2006)

TWA: 10 mg/m³ 65534 times per shift, 8 hour/hours. Form: Inhalable fraction

TWA: 0,8 mg/m³ 65534 times per shift, 8 hour/hours. Form: Respirable fraction

molybdenum disulfide

EH40-WEL (United Kingdom (UK), 9/2006). Notes: As Mo

TWA: 10 mg/m³ 65534 times per shift, 8 hour/hours.

STEL: 20 mg/m³ 65534 times per shift, 15 minute/minutes

Exposure controls

Occupational exposure controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection:

No respiratory equipment is required for normal use. In the case of extreme temperatures, a dry residue will result when the grease & oils burn off. Where workers may be exposed to the dust during removal of the film use of air-purifying respirators or dust masks is suggested.

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9. Physical and chemical properties

Physical state:

Liquid (gel)

Color:

Copper / bronze

Odor:

Petroleum pungent

pH:

Neutral

Boiling point:

<316°C (600.8°F)

Melting point:

260°C (500°F)

Flash point:

Open cup: 221°C (429.8°F)

Flammability (solid, gas):

Not applicable

Explosive properties:

Not applicable

Explosive limits:

Lower: 0.9% Upper: 7%

Oxidizing properties:

Not available

Vapor pressure:

<0.01 kPa (<0.08 mm Hg) (at 20°C)

Specific gravity:

Not available

Density:

1.15 g/cm³

Solubility:

Insoluble in cold water, hot water

Octanol/water partition coefficient:

Not available

JET-LUBE EXTREME

Viscosity:	Not available
Vapor density:	>5 (Air = 1)
Evaporation rate (butyl acetate = 1):	<0.01 compared with Butyl acetate
Auto-ignition temperature:	>260°C (500°F)

10. Stability and reactivity

Stability:	The product is stable
Conditions to avoid:	Keep away from sources of ignition. Keep away from heat.
Materials to avoid:	Not available
Hazardous Decomposition products:	These products are carbon oxides (CO, CO ₂), sulfur oxides (SO ₂ , SO ₃), etc.). Some metallic oxides.
Hazardous polymerization:	Not available

11. Toxicological information

Potential acute health effects

Inhalation:	No known significant effects or critical hazards as high viscosity makes inhalation unlikely.
Ingestion:	No known significant effects or critical hazards as grease results in gastric distress negating bioaccumulation concerns.
Skin contact:	No known significant effects or critical hazards.
Eye contact:	No known significant effects or critical hazards.
Potential chronic health effects	
Carcinogenicity:	No known significant effects or critical hazards.

California Prop 65:

None

Australian National Health & Safety Commission (NOSC):

None

Mutagenicity:

No known significant effects or critical hazards.

Reproductive toxicity:

No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation:	No known significant effects or critical hazards.
Ingestion:	No known significant effects or critical hazards.
Skin:	No known significant effects or critical hazards.
Target organs:	No known significant effects or critical hazards.
Other adverse effects:	Not available

12. Ecological information

Ecotoxicity data

Ingredient name

Ingredient name	Species	Period	Result
KOPR-KOTE	mysidopsis bahia (LC50)	96 hr/hrs	1980 mg/l
copper	Daphnia magna (EC50)	48 hr/hrs	0.0318 mg/l
	Daphnia magna (EC50)	48 hr/hrs	0.036 mg/l
Graphite	Daphnia magna (EC50)	48 hr/hrs	0.055 mg/l
	Pimephales promelas (LC50)	96 hr/hrs	0.0094 mg/l
	Pimephales promelas (LC50)	96 hr/hrs	0.0103 mg/l
	Pimephales promelas (LC50)	96 hr/hrs	0.0278 mg/l
	Fish (LC50)	96 hr/hrs	>1800 mg/l
	Algae (EC50)	72 hr/hrs	>1000 mg/l
Molybdenum disulfide	Skeletonema costatum (LC50)	72 hr/hrs	>1000 mg/l
	Scophthalmus maximus (EC50)	96 hr/hrs	>1000 mg/l
	Acartia tonsa (LC50)	48 hr/hrs	120 mg/l
Lubricating grease, petroleum based	Fish (LC50)	96 hr/hrs	>1800 mg/l
	Algae (EC50) ,biomass	72 hr/hrs	11 mg/l
	Algae (EC50) ,growth rate	72 hr/hrs	14 mg/l

Other ecological information

Persistence/degradability:

Ingredient name

Ingredient name	BOD	COD	ThOD
Lubricating grease, petroleum based	Not available	Not available	2.99 mg O ₂ /mg

Ingredient name

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Lubricating grease, petroleum based	Not available	Not available	15 % mineralisation in 28 days (BODIS)

Other ecological information

Mobility:

Not available

Other adverse effects:

No known significant effects or critical hazards.

Other adverse effects:

No known significant effects or critical hazards.

13. Disposal consideration

Methods of disposal:

The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Hazardous waste:

Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

JET-LUBE EXTREME

14. Transport information

Hazchem code 1Z

International transport regulations

Regulatory information	UN Number	Proper shipping name	Class	Packing group	Label	Additional information
US Dept of Transportation	UN3077	Tool Joint Compound				Approval CA2006100003
ADR/RID Class	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper)	9	III	9 Misc.	Hazard ID No. 90
ADNR Class	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper)	9	III	9 Misc.	Hazard ID No. 90
IMDG Class	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper)	9	III	9 Misc.	Hazard ID No. 90
IATA-DGR Class	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper)	9	III	9 Misc.	Hazard ID No. 90
Canada TDG	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper)	9	III	9 Misc.	Hazard ID No. 90
Australia ADG Code	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper)	9	III	9 Misc.	Reference SP-AU01

15. Regulatory information

Poison Schedule Not scheduled

EU Regulations

Risk Phrases: This product is not classified according to EU legislation.
Safety Phrases: S20/21 - When using do not eat, drink or smoke
 S28 - After contact with skin, wash immediately with plenty of water.
 S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection.
 S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets.
 Classification and labeling have been performed according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and the intended use. Industrial applications.

Product use:

Other EU regulations

Additional warning phrases: Safety data sheet available for professional user on request.

Restrictions on the marketing and use directive: Not applicable.

National regulations United Kingdom (UK)

COSHH: The use of this chemical product must be in compliance with provisions included in COSHH (1999) and COSHH Essentials (1999).

COSHH: The use of this chemical product must be in compliance with provisions included in COSHH (1999) and COSHH Essentials (1999).

US Regulations:

SARA 313 (40 CFR Part 372): **TSCA:** All components are listed. (See Section 3). **TSCA 12B Components:** None
 This material contains Materials which are subject to the reporting requirements.

SARA 311/312: None

CERCLA RQ: RQ: Copper: 5000 lbs.

OZONE DEPLETING CHEMICALS: None

TSCA REGULATORY: This material or its components are listed in the TSCA inventory.

RCRA Hazard class: N/A

Clean Air Act Sect 112 Hazardous Air Pollutants (HAPs): None **Volatile Organic Chemicals (VOCs):** Nil

State Right to Know:

New Jersey:	7440-50-8, 7782-42-5, 471-34-1
Pennsylvania:	7440-50-8, 7782-42-5, 471-34-1
Massachusetts:	7440-50-8, 7782-42-5, 471-34-1
Rhode Island :	7440-50-8, 7782-42-5, 471-34-1

Canadian Regulations: **DSL:** All components are listed. (See Section 3)

WHMIS: CLASS B-2: Not regulated

RoHs Compliance This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

16. Other information

Full text of R phrases referred to in sections 2 and 3 - United Kingdom (UK): R50 - Very toxic to aquatic organisms.

Full text of classifications referred to in sections 2 and 3 - United Kingdom (UK): N - Dangerous for the environment.


History

Date of printing: August 28, 2010

Date of issue: August 28, 2010

Date of previous issue: No previous validation

Version: 1

Prepared by: 

Name & Title Donald Oldiges, VP of Research & Development

Notice to reader:

JET-LUBE EXTREME

All practical steps have been taken to ensure this data sheet and the health, safety and environmental information contained in this document is accurate as of the date specified above. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. You should not use the product other than for the stated application or applications without seeking advice from us. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations in the country of use. Jet-Lube is not responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use have the duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. If this material is printed, circulated, distributed or copied in any manner, it is not to be modified without prior written permission, and further, it is to include the wording of the above disclaimer.