



# EZY-TURN® #8

## BALL & PLUG VALVE SEALANT WITH GROUND PTFE

### DESCRIPTION

**EZY-TURN® #8** Ball and Plug Valve Sealant is a vegetable oil based product containing a high percentage of ground PTFE. It is excellent for use in ball and plug valves that are worn or scored and have a tendency to leak. It is hydrocarbon and water resistant and can be injected through standard giant buttonhead fittings with a high pressure lubricator. **EZY-TURN #8** contains a blend of PTFE particle sizes designed to provide maximum sealing power. It is suitable for use as an injectable stem packing and as a thread sealant.

- Nontoxic
- Nonhazardous
- Contains PTFE
- Color: Blue Green
- Stops Leaks
- Water Resistant
- Hydrocarbon Resistant
- Injectable
- Biodegradable

### APPLICATIONS

**EZY-TURN #8** is an ideal sealant/lubricant for ball and plug valve applications where a worn, scored or leaking valve is encountered. The high percentage of ground PTFE in this product is designed to provide maximum sealing power and lubrication in problem situations. **EZY-TURN #8** is both oil and water resistant and can be used in virtually any oilfield, industrial or marine application where ball and plug valves are used. It can also be used in stuffing boxes, valve stems and as a packing and sealant for threads.

### SERVICE RECOMMENDATIONS

- Aliphatic Hydrocarbons
- Dilute Acids
- Dilute Alkalies
- Fuel Oils
- Crude Oils
- Crude Distillates
- Natural Gas
- Propane
- Kerosene
- Aqueous Solutions

### TEMPERATURE RANGE

0°F (-18°C) to 500°F (260°C)

**Recommended Cleanup:** Although conventional solvents like methanol, ethanol, IPA, chlorinated solvent, aromatic solvents, acetone and other ketones can be utilized, **JET-LUBE®** recommends its **EZY-OPEN™** or other safe oxygenated solvents. **EZY-OPEN** is a nontoxic, non-flammable, biodegradable lubricant and cleanser specifically designed for valve cleaning applications. It contains no components listed as federal hazardous wastes.

### PRODUCT CHARACTERISTICS

<b>Appearance</b>	
Bulk	Blue Green Paste
<b>Cone Penetration (ASTM D-217), mm x 10<sup>-1</sup></b>	
Bulk	220 - 250
<b>Density (lb/gal) Typical</b>	
Bulk	10.6
<b>Specific Gravity, Typical</b>	
Bulk	1.27
<b>Dropping Point (ASTM D-2265), °F (°C)</b>	
Bulk	None
<b>Oil Separation Wt. % (FTMS 791.B M.321.2) (ASTM D-6184)</b>	
Bulk	5.0 max
<b>Thickener</b>	
Bulk	Inorganic
<b>Flash Point (ASTM D-92) °F (°C)</b>	
Bulk	>400 (204)
<b>Temperature Range °F (°C)</b>	
Bulk	0 (-18) to 500 (260)
<b>pH Range</b>	
Bulk	2 - 9

**Note:** *Not for use with oxygen or strong oxidizers such as hydrogen peroxide or sulfuric acid.*

### PACKAGING

Part #	Container Size	Container
94516	5 gal/20L	Pail

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.



**Distributed by**

**1300-00-XTEX**  
**sales@xtex.com.au**  
**www.xtex.com.au**

VALVE VALVE VALVE VALVE VALVE