

# MAGIC WRENCH® SUPER PENETRANT



## DESCRIPTION

**MAGIC WRENCH®** Super Penetrant attacks rust and corrosion quickly and safely to free corroded parts, loosen nuts and aid in the disassembly of mechanical components. Versatile synthetic formula penetrates, lubricates, removes moisture and protects chains, cables, slides and other moving parts. Silicone free. Nonevaporative. Safe on all metals and plastics. Excellent for both food grade and non-food grade applications. Low V.O.C. (Volatile Organic Components) formula assures not only an environmentally responsible product, but more active ingredients to enhance product performance.

- NSF H-1 Registered #048230
- Penetrates Fast
- Synthetic Fluids
- Biodegradable
- Destroys Rust
- Lubricates
- Safe on Metal & Plastic
- Protects
- Low VOC Formula
- Silicone Free
- Ozone Safe
- Nonflammable (bulk)
- Nonevaporative

## APPLICATIONS

**MAGIC WRENCH** is a premium, synthetic product that may be used as a light machine oil, penetrating oil or rust preventive. Excellent for use on equipment such as chains, linkages, cams and slids, stirrups on bottle-filling machines, valves, pins, hinges, cables, etc. In addition, **MAGIC WRENCH** is an ideal product for the lubrication and conditioning of air tools.

NSF H-1 Registered (meets USDA 1998 H-1 Guidelines) for use in Federally Inspected Meat and Poultry Plants. Incidental Food Contact Permitted.

## PRODUCT CHARACTERISTICS

Appearance	Clear, pale yellow fluid w/faint odor
Fluid Type	Ester, PAO & White Oils
Propellant	Hydrocarbon
ISO Viscosity Grade	32
SAE Viscosity Grade	10
Density (lb/gal)	7.0 (bulk) 6.92 (aerosol)
Specific Gravity	0.84 (bulk) 0.83 (aerosol)
Flash Point (ASTM D-92)	>450°F (232°C)
Copper Strip Corrosion (ASTM D-130)	1B
Pour Point (ASTM D-97)	10°F (-12°C)
Spray Pattern (from 12" distance)	1" cone
Service Rating	-60°F (-51°C) to 350°F (177°C)

## PACKAGING

Part #	Container Size	Container
39543	16 oz/475 ml	Trigger Spray
39533	1 gal/4L	Pail

## LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.



**Distributed by**

**1300-00-XTEX**  
**sales@xtex.com.au**  
**www.xtex.com.au**

FOODGRADE  
FOODGRADE  
FOODGRADE  
FOODGRADE