

JET-LUBE[®] NCS-30[™]

NONCONDUCTIVE THREAD COMPOUND



DESCRIPTION

JET-LUBE[®] NCS-30 nonconductive thread compound is a premium quality, nonmetallic compound containing carbon based fibers and additives and other natural extreme pressure and anti-wear additives. These are blended into **JET-LUBE's** high temp calcium complex base grease. This new base grease offers the additional advantage of superior adhesion to wet steel surfaces, resistance to water wash-off, and most drilling muds. **Especially effective for invert or high-pH muds.**

- Excellent performance on high-chrome or nickel alloys
- Contains no metals
- Extreme-pressure additives provide additional protection against seizing and galling
- Nonconductive for MWD applications
- Provides maximum protection on **wedge thread** drill string connection designs
- High frictional properties ideal for casing drilling applications

NCS-30's solids package is formulated to prevent excessive circumferential makeup by increasing the coefficient of friction under compressive forces. As stress levels rise above 50% of yield, the friction factor increases, limiting downhole makeup. Full hydraulic joint efficiency is maintained allowing joint shoulder faces to mate completely without standoff or deformation. **NCS-30**, with frictional properties similar to **KOPR-KOTE[®]**, has been designed to utilize the makeup charts in API RP7G. Premium drill string connections such as HI-TORQUE[®] (HT), eXtreme[®] Torque (XT[®]), and XT-M[™] connections, etc., utilize make-up torques based upon thread compound friction factors of 1.0. Therefore, use the torque provided by the premium connection manufacturer. Adjusting make-up torque based on thread compound friction factor may still be advised.

For a "Yellow"-rated product, reference
NCS-30 ECF, Part No. 23715

PRODUCT CHARACTERISTICS

Thickener	Calcium Complex Petroleum
Fluid Type	Petroleum
Dropping Point (ASTM D-2265)	≥450°F (232°C)
Specific Gravity, typical	1.30
Density (lb/gal), typical	10.30
Oil Separation (ASTM D-6184)	<3.0
Wt. % Loss @ 212°F (100°C)	
Flash Point (ASTM D-92)	>430°F (221°C)
NLGI Grade	1½
Penetration @ 77°F (ASTM D-217)	290 - 320
Copper Strip Corrosion (ASTM D-4048)	1A, typical
Friction Factor*	
Relative to API RP 7G	1.15 (drill strings)
Relative to API RP 5A3	1.40 (relative to API-Mod)
Service Temperature	
Oilfield/Mining/Construction Drilling	-20°F (-29°C) to 500°F (260°C)
Industrial Anti-seize Applications	-65°F (-54°C) to 2600°F (1317°C)

Shelf Life: Minimum two years from manufacture date.

* Many factors such as pipe size, thread geometry, drilling mud contamination, etc. affect the friction factor. This is a relative number and in all applications experience and prior knowledge should be used to adjust make-up torque accordingly.

PACKAGING

Part #	Container Size	Container
16914	3.5 gal/14L	Pail

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.



Distributed by

1300-00-XTEX
sales@xtex.com.au
www.xtex.com.au

OILFIELD

OILFIELD

OILFIELD

OILFIELD

OILFIELD