

RENEW™ BELT DRESSING



DESCRIPTION

RENEW™ was developed to meet the demands of today's industrial grade belt dressing. **RENEW** eliminates problem belt slippage on all round, flat and "V" power transmission belts, auto fan belts and all industrial and farm machinery belt drives.

RENEW's dry, tacky film increases traction while permitting decreased belt tension for longer belt life. Can increase power up to 50%. **RENEW** is resistant to water wash-off and performs effectively under wet conditions. **RENEW** removes residual build-up and will not glaze or collect dirt and dust. May be applied while belts are in operation.

- Prevents Slippage
- Stops Squeaks, Squeals
- Extends Belt Life
- Resists Water Wash-Off
- Increases Power
- USDA/FDA Authorized

APPLICATIONS

Excellent for use on flat, round and V-style belts used on auto, industrial, dairy and farm belt drives. Chemically stable, non-drying and water resistant for maximum efficiency.

PRODUCT CHARACTERISTICS

Spray Pattern (from 12" distance)	Stream
Propellant	Hydrocarbon
Solvent Type	Petroleum Distillate
Resin	Resin Ester
Film Appearance	Clear to Light Amber Tacky Film
Dry Time	20 Minutes
Density (lb/gal)	6.7
Specific Gravity	0.80
Flash Point	>65°F (18°C)

PACKAGING

Code No.	Container Size	Container
50941	356 ml	Aerosol

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

NSF Reg. (P-1) for use in Federally Inspected Meat and Poultry Plants

Contains No 1:1:1 Trichloroethane, Freon TF or SARA Listed Ingredients



Distributed by

1300-00-XTEX
sales@xtex.com.au
www.xtex.com.au