

SILVER PLUS REGULAR

METALLIC ANTI-SEIZE



INDUSTRIAL
INDUSTRIAL
INDUSTRIAL
INDUSTRIAL

DESCRIPTION

JET-LUBE's SILVER PLUS REGULAR metallic anti-seize is designed to provide a protective film against galling and seizure over a wide range of applications. The micro-sized particles produce a smooth creamy consistency and allows it to quickly and easily coat fine threaded fasteners, small diameter fasteners all the way to large diameter fasteners.

SILVER PLUS REGULAR utilizes a water resistant, high temperature complex base grease as its carrier giving it superior "stay put" qualities. The complex thickener and highly refined base fluids allow for brushability down to -20°F (-29°C) and up to 450°F (232°C). The petroleum carrier, however, makes **SILVER PLUS REGULAR** unsuitable for oxygen service.

SILVER PLUS REGULAR contains micro-sized aluminum and copper as well as other nonmetallic extreme pressure and anti-wear particles. The metallic components make it very conductive and since the primary anti-seize particles is aluminum, it nearly eliminates the potential for galvanic corrosion. It also makes it the anti-seize of choice for components made of aluminum and its alloys.

- Shiny Silver Color
- Service Rating: -200°F (-129°C) to 1800°F (982°C)
- Brushable from -65°F (-54°C) to 400°F (204°C)
- Resists galvanic corrosion
- Permits reuse of fittings
- Resists alkaline and acid vapors

APPLICATIONS

SILVER PLUS REGULAR is excellent for use on bolts, nuts, gaskets, pipe fittings, guides and slides, valve assemblies, press fits, cylinder heads, chain drives, pump mountings, forging dies, manhole studs, exhaust manifold studs, etc.

PRODUCT CHARACTERISTICS

Thickener	Aluminum Complex
Fluid Type	Highly refined Petroleum
Appearance	Silver, buttery gel
Specific Gravity	1.15
Density (lb/gal)	9.6
Penetration (ASTM D-217)	310 - 350
Coefficient of Friction	0.08
Flash Point (ASTM D-92)	>430°F (221°C)
Copper Strip Corrosion	1B
Oil Separation, 100°C, 24 hrs.	<5%

PACKAGING

Code No.	Container Size	Container
69902	1/2 lb / 225 gm	Can

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.



Distributed by

1300-00-XTEX
sales@xtex.com.au
www.xtex.com.au